



## **Analyze and Design Of Green Computing In IT Organization Performance**

A.Seenuvasan<sup>1</sup> and J.R.Arunkumar<sup>2</sup>

Computer Science and Engineering

Dhaanish Ahmed College of Engineering, Anna University

Chennai-601 301, Tamilnadu, India

*Abstract: Till now, green computing research has mostly relied on few, short-term power capacity to illustrate the energy use of undertaking computing. This paper brings new and inclusive power datasets through power and deployment of the IT systems in the academic building. In this paper we collected some power data from many individual computing devices like CPU, MONITER, PRINTER etc., and have monitored a subset of CPU and network loads. This intense, long-term monitoring allows us to project the data to a detailed breakdown of temperature and electricity use across the building's computing systems. Our datasets endow with a chance to examine theory universally made in green computing. We show that power inconsistency both between parallel devices and over time for a particular device can lead to cost or savings approximately that are off by 12-17%. Extending the reporting of calculated devices and the duration considerably reduces temperature and electricity by Grid switch mode power supply (C-SMPS). Finally, our occurrence with collecting data and the subsequent analysis lead to a better understanding of how one should go about power classification revision.*

*Keywords: Green computing; AC to DC converter; Centralized SMPS; Distributed power; Reduce conversion losses*

### **I. Introduction**

Common sense tells us that there are prospect to reduce the energy waste of computing systems. Our electric power system was designed to move central station alternating current (AC) power, via high-voltage transmission lines and lower voltage distribution lines, to organization and businesses that used the power in incandescent computers, laptops, printers, lights other Alter native current devices. Today's end user apparatus and tomorrow's distributed renewable making requires us to reorganize this model. Electronic devices (such as Personal computers, laptops, changeable speed drives, and business appliances and equipment) need direct current (DC) input. However, all of these DC devices require conversion of the building's AC power into DC for utilize, and that conversion classically uses incompetent rectifiers. Moreover, spread renewable production (such as rooftop solar, wind) produces DC power but must be converted to AC to tie into the building's electric organism, only later to be re-converted to DC for many end uses. These AC-DC conversions (or DC-AC-DC in the case of rooftop solar) result in substantial energy losses.

One possible solution is a centralized DC convertor in DC power grid, which is a DC grid within a organization that minimizes or eliminates entirely these conversion losses. In the DC power grid system, AC power converts to DC when entering the DC grid using a high-competence rectifier, which then allocates the power in a straight line to DC equipment served by the DC grid. On typical, these systems trim down AC to DC conversion losses from an average loss of about 32% down to 10%. From individual converter and other distributed DC generation can be fed directly to DC equipment, via the DC power grid, without the double conversion loss (DC to AC to DC), which would be necessary if the DC production output was fed into an AC system.

Evaluate new green computing solutions remains vastly anecdotal. Until now, power characterization studies have either collected data at the macro scale of a whole building, lumping all plug loads into one number, or at the micro scale from a handful of computers and LCD monitors. Data at the macro scale is informative but difficult to act upon – it does not provide visibility into the computing components that can be made more energy efficient. Power data at the micro scale is great at providing a detailed characterization of single device. But fail to show how the individual data point relates to the full building energy use. The green computing research community can benefit from the availability of more extensive power measurements. For example, a single PC power measurement from 2004 has been used in papers as recent as 2010, citing it as a

representative value. The aforementioned paper gives the power draw of a 2002 Dell 2350 1.8 Ghz computer as 60 to 85 watts. A 2009 paper measured two desktops (102 and 72 watts, correspondingly) and said their capacity were consistent with prior data, citing. Later the same year, a characterization study used 100 watts per desktop plus LCD for some of its calculations, citing. In 2010, Light Green also referenced, stating that the typical PC draws 80–100 watts when active. The paper goes on to measure one PC (95W active) and uses it to calculate potential energy saving of their proposed solution. If we were to continue on citation trails like the one above, we risk using limited and possibly outdated data for new systems' evaluation. Fast-paced improvements in personal computing mean that some newer, more powerful PCs are also more power-hungry than the 60- to 100-watt range. In addition, enterprise environments are often heterogeneous and it is beneficial to have power measurements from a larger selection of devices. This paper helps fill the power data gap by characterizing energy data at the individual– and the building–scale levels.

The answers to these questions from the fundamental contributions of this paper: Detailed examination of where energy goes reveals that over 50% of the electricity is spent on converter AC to DC converter. PC's account for 17% of the bill despite the fact that their utilization is very low. Networking equipment comes at 3.5% and shows no temporal changes despite variations in traffic load. Data analysis shows that estimating saving based on a few isolated desktop measurements is prone to errors due to the wide spread of PC power draws. Assuming that a day of power is representative and using it to calculate yearly values can be off by as much as 20%. Our deployment and data studies expose the relative importance of device coverage versus duration of deployment. Once a deployment is past the first month of data collection, one must prioritize the 'what to measure' question over the time scale of the study. The rest of this paper reviews the current state of green computing data before diving into the analysis of the Power grid datasets. Along the way, it confirms or refutes a number of anecdotal observations, stressing the need for empirical data. The paper closes with guidelines for the design of future energy characterization studies.

## II. Background

Up until recently, the green computing community has had to rely on limited energy datasets, requiring researchers to make various explicit and implicit assumptions about the energy behavior of computing systems. This section discusses some of the different ways in which related work has procured, used, and analyzed power data in the context of evaluating systems' research. At the end of the section, we formulate four common assumptions made in the context of green computing.

A modeling approach that takes system subcomponents into consideration was used SMPS in CPU. Instead of collecting measurement with a meter, the authors use hardware components power models and software counters to calculate the power draw of a PC. This methodology was able to predict the power use of one machine based on a different one with 20% accuracy, indicating that even more sophisticated techniques that take device subcomponents into consideration will show error in estimation when assuming that similar equipment has similar power or usage behavior.

The industry drive toward less important, lighter and more resourceful electronics has led to the development of the Switch Mode Power Supply (SMPS). There are several topologies commonly used to put into service SMPS. This submission note, which is the primary of a two-part sequence, explains the essentials of unusual SMPS topologies. Applications of unusual topologies and their pros and cons are also thrash out in aspect. This application note will channel the user to decide on an suitable topology for a given function, while given that useful in sequence regarding selection of electrical and electronic mechanism for a given SMPS design.

### A. Advantages

- Reliability; security; storage; distributed generation
- energy efficiency; sustainability; renewable inputs
- IT/communications leverage/full cyber-security
- load awareness; demand side management; plug-in vehicles
- lowering unnecessary barriers to achieving the above
- Each of these goals can be advanced through the use of DC micro grids and often at

Lower cost with greater effectiveness than measures applied to the greater AC grid. The national power grid system in the India and around the world was not designed to handle the energy demands of the modern economy. To meet the contemporary Needs of the grid's organizations today, we should consider the tools available through DC micro grids, which can optimize the use of electronic devices, electrical storage, and distributed generation.

### III. Measuring Computing Power Accurately

The prior section pointed out four common assumptions in measuring computing power which can lead to inaccurate results. The results from Powernet, however, represent only one point in time. As computing continues to evolve, green computing. Need to periodically re-measure energy consumption and waste. This raises the follow-up question: 'Given limited time, money, and effort, how should one measure computing system energy consumption in order to minimize error?' This section presents methodology considerations to guide future green computing research.

#### A. Characterization

Our electric power system was designed to move central station alternating current (AC) power, via high-voltage transmission lines and lower voltage distribution lines to Organization Computer equipments. Today's organizations equipment and tomorrow's distributed renewable generation requires us to rethink this model. Electronic devices (such as computers, florescent lights, variable speed drives, and many other household and business appliances and equipment) need direct current (DC) input. However, all of these DC devices require conversion of the building's AC power into DC for use, and that conversion typically uses inefficient rectifiers. Moreover, distributed renewable generation (such as rooftop solar) produces DC power but must be converted to AC to tie into the building's electric system, only later to be re-converted to DC for many end uses. These AC-DC conversions (or DC-AC-DC in the case of rooftop solar) result in substantial energy losses.

One of possible solution is a DC micro grid, which is a DC grid within a building (or serving several buildings) that minimizes or eliminates entirely these conversion losses. In the DC micro grid system, AC power converts to DC when entering the DC grid using a high-efficiency rectifier, which then distributes the power directly to DC equipment served by the DC grid. On average, this system reduces AC to DC conversion losses from an average loss of about 32% down to 10%.<sup>2</sup> In addition, roof top photovoltaic (PV) and other distributed DC generation can be fed directly to DC equipment, via the DC micro grid, without the double conversion loss (DC to AC to DC), which would be required if the DC generation output was fed into an AC system.


#### B. DC micro grid

A micro grid possesses independent controls, and intentional islanding takes place with minimal service interruption. These two definitions work easily in both the AC and DC domain, so we will borrow them both. DC micro grids can be deployed in a portion of a building, building-wide or covering several buildings. We will refer to these systems as "DC micro grids" in the balance of this paper.

### IV. Architecture for Centralized SMPS AC/DC Converter

The architecture of the proposed system describes the centralized power architectures can get quite complex and specialized, most are either derived from or combinations of four basic configurations.

**Figure 1. Centralized SMPS AC/DC Converter**



Centralized power, such as an approach, represents a converse technique. In a distributed power system the system's power requirements are allocated to a number of smaller power processing units which are then distributed throughout the system in a variety of architectures, usually with the intent of bringing power processing closer to where the power will be used. While the ultimate extension of this concept is the "on-card" regulator or power supply, many other solutions for distributing power processing tasks are common. Before

discussing the various architectures, however, it is helpful to understand the motivation for considering distributed power.


### Distributed Power Architectures

While distributed power architectures can get quite complex and specialized, most are either derived from or combinations of four basic configurations which are shown in Figure 2. These are: parallel, series, split source, or split load. It should be recognized that in addition to different inter connections, each of these approaches represents a solution to a different Set of objectives. A description of these architectures and their characteristics is given below:

#### Paralleling

Paralleling power modules infers a common source and load. This usually means retaining a Central location where a single high power supply is replaced with a grouping of paralleled lower power modules. While the power processing is distributed, it may not be distributed very far. Parallel connections are often generated by the need for standardization and redundancy rather than reducing distribution losses.

**Figure 2: Paralleling with Current Mode Control**




With higher reliability as an objective, equalizing stresses by insuring load sharing between modules is usually required. Configuring power converters for current sharing when paralleled is not a trivial problem but ICs for that purpose as well as the use of current-mode control methods provide ready solutions. It should be noted that most approaches to equal current sharing require at least one more interconnection between modules in addition to the common source and load connections. Figure 3 shows current mode control where the output of the voltage sensing error amplifier is used by the PWM modulator to control output inductor current. By using a single error amplifier to control all the paralleled modulators, equal currents from each module can be assured.

#### Load splitting

The most common understanding of distributed power assumes split loads Where different portions of the system are each powered by their own power processing unit. An illustration of load splitting is shown in Figure 6. Note that this gives innumerable options in terms of dividing up the loads and the corresponding requirements on the power processing units.

**Figure 3 -Splitting Loads**



The final step is to take the set of biased dimensions and extrapolate to whole system power. Our familiarities with Power net have decorated the need for data additional than power and consumption measurements. If

extrapolation is to be successful, one also wants metadata in the form of equipment inventories and descriptions. Surprisingly, such metadata is not nearly as complete and readily available as we had hoped. Rather, we had to resort to indirect sources such as cross-correlating networked device registrations with active IPs on the network. In the future, green computing researchers should encourage IT personnel to keep updated and detailed records of what equipment is added to a building.

## V. Conclusion

Characterizing the energy use of organization computing systems is the first step toward identifying opportunities for improvement. Extensive, empirical data allow researchers to better quantify the problems they are tackling and the potential impact of their proposed solutions. Power net has provided such data and has shed light on some of the assumptions that we make when faced with the lack of solid measurements. Despite our best attempts to cover as many computing systems for as long as possible, the Power net data remain but a single study. While the exact breakdown of energy use and waste might shift from building to building, the overarching methodology and data analysis lessons remain. Going forward, green computing research has not only a reference dataset to use but also a blueprint for how to characterize enterprise building power given limited time and resources.

The DC power grid concept represents a decentralization of the idea of the grid, and one that advances the goals of the current Smart Grid overhaul. The DC power grids begins to change the paradigm from a centralized generation and distribution system of power delivery to a system that is more flexible and more accommodating of the load that has come to be: one that is more electronic, more ubiquitous, and more essential to our economy and our culture. DC power grids can create power systems that are more efficient and more compatible with the fastest growing segment of the load today: electronic devices. In turn, by catering to the needs of digital devices, we naturally expand the networks in which they operate (both power and control) to benefit from – or indeed require – redundant operation that is primarily available today through the other ubiquitous DC device, the battery.

## VI. References

- [1] Maria Kazandjieva, Brandon Heller, Omprakash Gnawali, Philip Levis, and Christos Kozyrakis- Green Enterprise Computing Data: Assumptions and Realities, 978-1-4673-2154-9/12/\$31.00 c 2012 IEEE.
- [2] Mohammad Kamil, Microchip Technology Inc.– Switch Mode Power Supply (SMPS) Topologies, 2007 Microchip Technology Inc.
- [3] Paul Savage, Robert R. Nordhaus, and Sean P. Jamieson, Analyses written at the request of REIL, yale school of forestry & environmental studies.
- [4] Single Phase Multifunction Energy Metering IC with di/dt Input.
- [5] Department of Energy, *Annual Energy Review*, October 2011.
- [6] Y. Agarwal, S. Hodges, R. Chandra, J. Scott, P. Bahl, and R. Gupta. Somniloquy: Augmenting Network Interfaces to Reduce PC Energy Usage. In Proc. Networked Systems Design and Implementation, 2009.