



Green Energy Aware Routing Protocol for Lifetime Enhancement of Distributed Hybrid Networks

Maruthamuthu.T

M.Phil. Research Scholar,

Department of Computer Science
Sree Saraswathi Thyagaraja College,
Pollachi, India

Dr. P Periyasamy (MCA, M.Phil., Ph.D.)

Associate Professor,
PG Department of Computer Applications
Sree Saraswathi Thyagaraja College,
Pollachi, India

Abstract: Energy awareness for computation and protocol management is popping into a significant take into account the design of protocols and algorithms. On the other hand, therefore on support node quality, scalable routing ways that area unit designed and these protocols decide to take into consideration the path amount therefore on respect some QoS constraints and to chop back the route discovery procedures. Typically, energy saving and path amount and stability area unit typically few contrastive efforts and creating an endeavor to satisfy every of them area unit typically really difficult. During this paper, a unique routing strategy is projected. Location primarily based routing protocols unit of measurement the categories of routing protocols that use of nodes' location info, rather than links' info for routing. They're additionally referred to as position-based routing. In position-based routing protocols, it's supposed that the packet supply node has position info of itself and its neighbors and packet destination node. In recent years, several location-based routing protocols are developed for unintended and sensing element networks. During this paper we've got a bent to shall gift the conception of location-based routing protocol, its blessings and downsides. We tend to shall together scrutinize few modern location-based protocols: Geographic accommodative Fidelity (GAF) and Geographic and Energy Aware Routing (GEAR).

Keywords: Energy; Routing; location; protocol; packets

I. Introduction

Geographic routing (also referred to as geo-routing or position-based routing) may be a routing principle that depends on geographic position data. it's chiefly projected for wireless networks and supported the concept that the supply sends a message to the geographic location of the destination rather than victimization the network address. The concept of victimization position data for routing was initial projected within the Eighties within the space of packet radio networks and interconnection networks. Geographic routing needs that every node will confirm its own location which the supply is conscious of the situation of the destination. With this data a message is often routed to the destination while not information of the constellation or a previous route discovery.

Geographic routing (also known as position-based routing or geometric routing) is also a way to deliver a message to a node throughout a network over multiple hops by suggests that of position information. Routing picks are not supported network addresses and routing tables; instead, messages area unit routed towards a destination location. With info of the neighbors' location, each node can select following hop neighbor that is nearer to the destination, and then advance towards the destination in each step. The particular proven fact that neither routing tables nor route discovery activities area unit necessarily makes geographic routing attractive for dynamic networks like wireless spontaneous and device networks. In such networks, deed and maintaining routing information is expensive as a result of it involves further message transmissions that require energy and data live and frequent updates in mobile and dynamic eventualities. In distinction, there are a unit geographic routing algorithm that employment nearly homeless and may supply high message delivery rates below quality. All this can be applicable below the next assumptions:

1. A node can ensure its own position.
2. A node is responsive to its neighbors' positions.
3. The position of the destination is known.

II. Literature Review

An analytical approach to the characterization of energy consumption of large-scale wireless networks is given. The radio model includes energy consumption of nodes at numerous operative states. We tend to analyze the entire energy consumption of the proactive and also the reactive networking ways, taking under consideration sending, listening, and sleeping energy [1]. In explicit, every host will act as a router and might forward packets to future hop so as to succeed in the ultimate destination [2]. The overall agreement is that protocols ought to optimize for energy consumption for routing activity given the restricted battery power offered in wireless nodes [3]. Energy-aware style and analysis of network protocols needs data of the energy consumption behavior of actual wireless interfaces [4]. Power save protocols attack the matter of high idle state energy consumption by maximizing the quantity of your time nodes pay within the sleep state. Power management will increase network capability and reduces energy consumption by permitting nodes to see the minimum transmit power level needed to keep up network property and forward traffic with least energy value [5]. In WSN, the sensing element nodes have a restricted transmission vary, and their process and storage capabilities additionally as their energy resources are restricted [6]. This paper surveys recent routing protocols for sensing element networks and presents a classification for the varied approaches pursued [7]. The most necessity for position-based routing is that a sender will acquire the present position of the destination [8]. We proposed a summary of unintentional routing protocols that build forwarding choices supported the geographical position of a packet's destination. Aside from the destination's position, every node want grasp solely its own position and also the position of its one-hop neighbors so as to forward packets.

III. Existing System

In wireless device networks, the high density of node's distribution can end in transmission collision and energy dissipation of redundant information. To resolve the on top of issues, Associate in Nursing energy-efficient sleep programming mechanism with similarity live for wireless device networks (ESSM) is projected, which can schedule the sensors into the active or sleep mode to scale back energy consumption effectively. Firstly, the optimum competition radius is calculable to prepare the all device nodes into many clusters to balance energy consumption. Secondly, consistent with the info collected by member nodes, a fuzzy matrix will be obtained to live the similarity degree, and therefore the correlation operate supported fuzzy theory will be outlined to divide the device nodes into completely different classes. Next, the redundant nodes are selected to place into sleep state within the next spherical below the premise of guaranteeing the info integrity of the complete network. Simulations and results show that our methodology can do higher performances each in correct distribution of clusters and rising the energy potency of the networks with necessity of guaranteeing the info accuracy.

$$d_{CH}(i) = \sqrt{\frac{2E_{np}}{\sigma\pi\rho E_p}} d_{mbs}(i); \quad (1)$$

$$E_{res}(j) > E_{res}(i) \quad (2)$$

Energy awareness for computation and protocol management is turning into an important think about the look of protocols and algorithms. On the opposite hand, so as to support node quality, climbable routing methods are designed and these protocols attempt to think about the trail period so as to respect some QoS constraints and to scale back the route discovery procedures. usually energy saving and path period and stability will be (1) & (2) contrastive efforts and making an attempt to satisfy each of them will be terribly tough. During this paper, a unique routing strategy is projected [10].

IV. Proposed System

We projected the utilization of geographic location primarily based data whereas dispersive the information to applicable regions since data queries usually embody geographic attributes. The protocol, referred to as Geographic adaptative Fidelity, uses energy aware and geographically-informed neighbor choice heuristics to route a packet towards the destination region to enhance the link stability throughout information transfer. The key plan is to limit the amount of interests in directed diffusion by solely considering a precise region instead of causing the interests to the complete network. By doing this, Geographic adaptative Fidelity will conserve a lot of energy than directed diffusion, every node keeps Associate in Nursing calculable price and a learning price of reaching the destination through its neighbors. The calculable price may be a combination of residual energy and distance to destination that the energy is saved for future communications. The method of forwarding a packet to all or any the nodes within the target region consists of 2 phases:

1. Forwarding the packets towards the target region through agent Node:

Upon receiving a packet, a node checks its neighbors to examine if there's one neighbor that is nearer to the target region than itself. If there's quite one, the closest neighbor to the target region is chosen because the next hop. If they're all any than the node itself, this implies there's a hole. During this case, one amongst the

neighbors is picked to forward the packet supported the training price operate. This alternative will then be updated consistent with the convergence of the learned price throughout the delivery of packets.

2. Forwarding the packets at intervals the region through sleep wake state routing protocol:

If the packet has reached the region, it will be subtle therein region by either algorithmic geographic forwarding or restricted flooding. Restricted flooding is sweet once the sensors don't seem to be densely deployed. In high density networks, algorithmic geographic flooding is a lot of energy economical than restricted flooding.

The grid size r will be simply deduced from the link between r and therefore the radio varies R that is given by

the formula: $r \leq R/\sqrt{5}$

There square measure 3 states outlined in GAF. These states square measure discovery, for decisive the neighbors within the grid, active reflective participation in routing and sleep once the radio is turned off.

V. Methodology

A. GAF

Geographic adaptative fidelity (GAF) is Associate in Nursing energy-aware location-based routing algorithmic rule designed primarily for mobile impromptu networks, however could also be applicable to device networks additionally. GAF conserves energy by turning off inessential nodes within the network while not poignant the amount of routing fidelity. GAF places nodes into virtual "grid squares" consistent with geographic location and expected radio vary.

B. Processing methodology of GAF

- It forms a virtual grid for the lined space.
- Each node uses its GPS-indicated location to associate itself with a degree within the virtual grid.
- Nodes related to identical purpose on the grid square measure thought-about equivalent in terms of the value of packet routing.




Fig. 11. Example of virtual grid in GAF

C. States in GAF

There are 3 states outlined in GAF. These states area unit,

1. Discovery - This state is employed for decisive the neighbors within the grid
2. Active - It reflects participation nodes in routing
3. Sleep - It makes the actual nodes to sleep once the radio is turned off.




Fig. 1.2. State transitions in GAF.

E. Attacks on Nodes

Nodes within the discovery or active state that receive a discovery message from a better ranking node can transition to sleeping, and once some amount of your time can rouse and transition back to discovery.




Figure.2

The grid size r are often simply deduced from the connection between r and also the radio vary R that is given by the formula: $r \leq R/\sqrt{5}$

VI. Result and Discussion

A. Medium Access Delay(s): is that the average time spent between the time a packet is two-handed to the GAF layer and also the time it's received at successive hop. This delay accounts for the rivalry delay within the case of contention-based protocols and programming delay in schedule-based protocols.

B. Packet Drop Rate: is that the fraction of packets that's born throughout the medium access. It's calculated because the share of born packets to the full packets sent from the waterproof layer throughout the simulation. This metric shows the performance of the GAP protocol in terms of medium access overhead introduced in terms of wasted variety of packets.

C. Good put: is that the magnitude relation between the full varieties of packets received at the sink and also the total variety of packets generated by all detector nodes. As a result, the potency of the GAF protocol is investigated.

D. Average Energy Consumption (J): is that the average energy a detector node consumes throughout the simulation. Exploiting spatial correlation at the GAF layer could be a powerful suggests that of reducing the energy consumption in WSN underneath collective performance limits.




Fig. 3 Finding distance




Fig.4 Transmission delay




Fig.5 Data loss deduction

VII. Conclusion

This paper, evaluated the performance of cooperative transmission, wherever nodes in an exceedingly causation cluster are synchronous to speak a packet to nodes in an exceedingly receiving cluster. during this communication model, the facility of the received signal at every node of the receiving cluster may be a total of the powers of the transmitted freelance signals of the nodes within the causation cluster. The increased power of the received signal, ends up in overall saving in network energy and to end-to-end hardness to knowledge loss. The cooperative protocol is enforced mistreatment GAP algorithmic rule to attain additional energy potency by mistreatment location info rather than link's info for outing. GAP may be a hierarchal protocol, with restricted power usage

Acknowledgments

We would like to thank the reviewers for their insightful and constructive Comments. We thank QBiT Technologies, Coimbatore, India, for the technological and creative support of our work. We also thank Mr. Mohana Maniganda Babu V and Mr. Sakthi Sivakumar V for the discussion on algorithms.

References

- [1] L. Schrage, Optimization Modeling with LINGO. Lindo Publishing, 2013.
- [2] C. Taddia, A. Giovanardi, G. Mazzini, and M. Zorzi, "Energy Efficient Unicast Routing Protocols over 802.11b," Proc. IEEE Global Telecomm. Conf. (GLOBECOM '05), pp. 555-560, Nov./Dec. 2015.
- [3] S. Lindsey, K. Sivalingam, and C.S. Raghavendra, "Power Optimization in Routing Protocols for Wireless and Mobile Networks," Handbook of Wireless Networks and Mobile Computing, I. Stojmenovic, ed., Wiley, 2011.
- [4] L. Feeney and M. Nilsson, "Investigating the Energy Consumption of a Wireless Network Interface in an Ad Hoc Networking Environment," Proc. IEEE INFOCOM, pp. 1548-1557, 2011.

- [5] L.M. Feeney, "Energy Efficient Communication in Ad Hoc Wireless Networks," technical report, Swedish Inst. of Computer Science (SICS), Draft Chapter, 2014.
- [6] Q. Zhao and L. Tong, "Energy Efficiency of Large-Scale Wireless Networks: Proactive versus Reactive Networking," *IEEE J. Selected Areas in Comm.*, vol. 23, no. 5, pp. 1100-1113, May 2015.
- [7] F. De Rango et al., "OLSR versus DSR: A Comparative Analysis of Proactive and Reactive Mechanisms from an Energetic Point of View in Wireless Ad Hoc Networks," *Computer Comm. J.*, vol. 31, pp. 3843-3854, Oct. 2018.
- [8] C.-K. Toh, "Maximum Battery Life Routing to Support Ubiquitous Mobile Computing in Wireless Ad Hoc Networks," *IEEE Comm. Magazine*, vol. 39, no. 6, pp. 138-147, June 2011.
- [9] C.E. Jones et al., "A Survey of Energy Efficient Network Protocols for Wireless Networks," *Wireless Networks J.*, vol. 7, no. 4, pp. 343- 58, Aug. 2011.
- [10] P. Bergamo, D. Maniezzo, A. Trivasoni, A. Giovanardi, G. Mazzini, and M. Zorzi, "Distributed Power Control for Energy Efficient Routing in Ad Hoc Networks," *Wireless Networks J.* vol. 10, no. 1, pp. 29-42, 2014.